



**GATOR XP OIL & GREASE REMOVER
FOR CONCRETE PAVERS, WETCAST & NATURAL STONES**

TDS Revision Date (dd/mm/yyyy): 18/04/2019

TECHNICAL DATA SHEET

- Update:** April 18, 2019
Make sure you have an updated data sheet on hand.
Canada and U.S. dial 1-855-847-7767 or (450) 624-1611
- Description:** **Gator Clean XP Oil and Grease Remover** easily removes tough stains such as motor oil, cooking oil & grease. Just shake the bottle, spread it on the stain, let it dry, and sweep it up. Use it on concrete, brick & stone. Do not use on asphalt (blacktop). Not recommended for synthetic oil stains. **Gator Clean XP Oil and Grease Remover** is biodegradable and phosphate-free.
- Coverage:** • Approximately 6 square feet (.56 square meters).
- For use on:** Concrete pavers, wetcast & natural stones.
- Features:**
- Easily lifts & absorbs embedded oil stains as it dries from liquid to powder
 - No scrubbing
 - No rinsing
 - No mess
- Please note:** Before using on sealed, colored, or painted surfaces, ALWAYS TEST the product on a small hidden area of approximately 4 square inches (26 sq. cm.) to ensure the results will meet your expectations. Prior use of other cleaners may inhibit performance. If applied on sealed pavers it may damage the seal. Visit www.AllianceGator.com for cleaning tips.
- Application instructions:**
- Always test a small area before use. Do not use on wet surfaces. Use above 40°F (4°C) and provide maximum ventilation.
1. Shake bottle before applying to stain, extending one inch beyond perimeter of the stain. Coating thickness should be 1/8".
 2. Allow to dry completely to powder. Wait 12 to 24 hours, depending on temperature, humidity and ventilation.
 3. Sweep it up. If area still appears dark, provide adequate ventilation and allow moisture to evaporate.
 4. If stain remains, reapply, scrub with hard bristled brush, and repeat steps 2 and 3.
 5. Rinse off any remaining residue with water.
- Caution:** Provide maximum ventilation during use. Do not mix with other chemicals. KEEP OUT OF REACH OF CHILDREN AND PETS. Avoid contact with grass or plants. Avoid inhalation of dust when sweeping. Avoid eye and skin contact. EYE CONTACT: Flood eyes repeatedly with water and call physician. IF SWALLOWED: Do not induce vomiting. Drink a glass of water and call physician immediately.



**GATOR XP OIL & GREASE REMOVER
FOR CONCRETE PAVERS, WETCAST & NATURAL STONES**

TDS Revision Date (dd/mm/yyyy): 18/04/2019

WARRANTY :

Alliance Designer Products Inc. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of Alliance Designer Products Inc. is to refund the purchase price. Proof of purchase is required for any claim. Alliance Designer Products Inc. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, Alliance Designer Products Inc. excludes any implied warranty of quality, merchantability or fitness for purpose.

*Please store container at above 32°F / 0°C.

DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. CAUSES BURNS. Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Wear a mask, impervious gloves and safety glasses. Use only in a well-ventilated area. Handle with care.

FIRST AID TREATMENT:

Contains Potassium hydroxide, Silicic acid, sodium salt and Phosphoric acids. If swallowed, call a Poison control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.



SEE THE INSTALLATION VIDEO
ON ALLIANCEGATOR.COM