

Premier™ Retaining Wall Blocks



The 4 x 2" anchor bar on the underside of Premier 8 creates an automatic 1" (7°) setback with the highest shear resistance in the industry.

Manufactured in accordance with ASTM C1372.



Pound for pound, Premier 6 and 8 are unlike any other SRW blocks.

This revolutionary block design makes Premier the most efficient SRW blocks ever. Weighing nearly half that of comparable SRW's, they beat all other block systems for freight efficiencies and ease of construction.

- Easy to handle for increased efficiencies in the field
- No cumbersome/expensive pins or clips
- Capable of tight radius turns
- Significant freight advantages, more sq. ft. per truckload



Block	Size	Face Area	Weight	Units/Layer	Layers	Units/Pallet	Pallet Weight
Premier 8	18 x 12 x 8" H	1 sq. ft.	54 lbs.	9	6	54 (54 sq. ft.)	2,966 lbs.
Premier 8 Corner	18 x 9 x 8" H	1 sq. ft.	105 lbs.	8	5	40 (40 sq. ft.)	4,250 lbs.
Premier 6	18 x 12 x 6" H	.75 sq. ft.	42 lbs.	9	6	54 (40.5 sq. ft.)	2,318 lbs.
Premier 6 Corner	16 x 8 x 6" H	.67 sq. ft.	63 lbs.	15	6	90 (60.3 sq. ft.)	5,720 lbs.



Hi-Way Concrete Products, Inc.
2746 Cranberry Hwy, Wareham, MA 02571
Phone: (508) 295-0834 • www.hiwayconcrete.com

©Copyright 2023. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners. Rockwood Retaining Walls products are made worldwide under license from Rockwood Retaining Walls, Inc. US and international patents issued and pending. The information presented here has been prepared for the benefit of customers interested in Hi-Way Concrete Products Inc., it was reviewed carefully prior to publication. Hi-Way Concrete Products Inc. assumes no liability for its accuracy or completeness. Final determination of the suitability of any information or material for the use contemplated, or for its manner of use, is the sole responsibility of the user. 823